



TUBERIA ASTM

Norma ASTM: Tubos redondos soldados y sin soldadura fabricados según ASTM-312 (ANSI B 36.10- B 36.19 EN10217-7)

Certificados: EN10204/3.1.B

PULGADAS	DIAMETRO EXTERIOR mm.	ESPEORES/PESOS: SCHEDULE					
		SCH-10	KG/MTR	SCH-40/STD	KG/MTR	SCH-80/XS	KG/MTR
1/4"	13,70	1,65	0,50	2,24	0,64	3,02	0,82
3/8"	17,10	1,65	0,64	2,31	0,85	3,2	1,12
1/2"	21,30	2,11	1,02	2,77	1,29	3,73	1,62
3/4"	26,70	2,11	1,30	2,87	1,70	3,91	2,25
1"	33,40	2,77	2,12	3,38	2,54	4,55	3,25
1 1/4"	42,20	2,77	2,72	3,56	3,44	4,85	4,50
1 1/2"	48,30	2,77	3,15	3,68	4,10	5,08	5,42
2"	60,30	2,77	3,95	3,91	5,50	5,54	7,50
2 1/2"	73,00	3,05	5,30	5,16	8,70	7,01	11,50
3"	88,90	3,05	6,50	5,49	11,40	7,62	15,30
3 1/2"	101,60	3,05	7,50	5,74	13,70	8,08	18,70
4"	114,30	3,05	8,50	6,02	16,20	8,56	22,40
5"	141,30	3,4	12,40	6,55	22,00	9,53	40,30
6"	168,30	3,4	14,00	7,11	28,50	10,97	42,70
8"	219,10	3,76	19,95	8,18	43,20	12,7	64,80
10"	273,00	4,19	27,80	9,27	61,00	12,7	81,63
12"	323,80	4,57	36,00	9,52	73,80	12,7	97,44
14"	355,60	4,78	41,35	9,52	81,30	12,7	107,40
16"	406,40	4,78	47,30	9,52	93,27	12,7	123,31
18"	457,00	4,78	53,30	9,52	105,17	12,7	139,16
20"	508,00	5,54	68,50	9,52	117,15	12,7	155,13
24"	610,00	6,35	95,50	9,52	141,12	12,7	187,07